

B200FLF Blinking Beacon

The B200FLF is a 5W filament lamp blinking beacon/indicator.
The B200 series is comprised of a Xenon strobe beacon, permanent filament bulb, blinking filament bulb and a permanent LED array beacon version.

The surface mount base can also be supplied with a right angle bracket or with a pole mounted assembly.


Features

- Bayonet fixing lens.
- Anti-tamper locking screw.
- Stainless steel fixings.

Approvals

- GOST-R certificate: POCC GB.JB05.H00144.





Specification

Light source:	Filament lamp BA9s
Light output:	5W
Flash frequency:	1Hz
Candela:	2 cd* (peak/effective intensity)
Lens colours:	Amber, Blue, Clear, Green, Red & Yellow
Lens type:	Prismatic (standard) or plain
Mounting:	Surface mount (right angle or pole mount accessories available)
Ingress protection:	IP65
Housing material:	High impact UL94 V0 (f1) PC
lens material:	High impact UL94 V0 (f1) PC
Terminals:	0.5 to 1.5mm ²
Operating temp:	-25 to +50°C [-13° to +122°F]
Storage temp:	-40 to +70°C [-40° to +158°F]
Relative humidity:	90% at 20°C [68°F]
Weight:	78g/1.71lbs
*Candela measurements representative of performance with clear lens at optimum voltage.	

Part Codes

Version:	Wattage:	Part code:
12V dc	5W	B200FLF012B/[x]
24V dc	5W	B200FLF024B/[x]
48V dc	5W	B200FLF048B/[x]
115V ac	5W	B200FLF115B/[x]
230V ac	5W	B200FLF230B/[x]
[x] = Lens colour:		A: Amber B: Blue C: Clear G: Green R: Red Y: Yellow

Current Consumption

Version:	Current mA:
12V dc	500mA
24V dc	250mA
48V dc	120mA
115V ac	50/60Hz 35mA
230V ac	50/60Hz 25mA

AUTHORIZED DISTRIBUTOR:
GasDetectorsUSA.com
Houston, Texas USA
sales@GasDetectorsUSA.com
832-615-3588