



# GasCheck G

# Rapid, accurate detection of low level leaks.



# GasCheck G rapidly and accurately detects almost any gas or gas mixture down to highly sensitive levels.

# Best available leak detection

- · Fast, accurate leak detection at highly sensitive levels
- Detects almost any known gas or gas mixture
- Particularly sensitive to ammonia, argon, butane, helium, hydrogen and SF6
- Reliable, stable, repeatable readings

# Ease of use

- Simple, one handed operation
- · Large, clear LCD back lit display for easy viewing
- Graphical icon menu
- Conveniently calibrated against helium

# Flexibility

- Choice of readings in cc/sec, g/yr, mg/m<sup>3</sup>
- Easily upgradeable throughout the range

# Low cost operation

- · Inexpensive consumables and parts
- Free 2 year warranty when instrument registered online

Unrivalled Detection.

www.ionscience.com

GasCheck G V1.5. This publication is not intended to form the basis of a contract and specifications can change without notice.

Designed for the search and location of gas leaks, GasCheck G has an advanced micro thermal conductivity sensor for fast, effective detection of almost any gas or gas mixture.

Robust and reliable, GasCheck G provides stable, repeatable readings of the detected gas. The instrument's LCD display, LED indicator and audible sounder clearly indicate the leak present.

GasCheck G automatically zeros to the ambient air around it when switched on and is ready to detect immediately. The instrument's easy to use graphical interface and intuitive keypad allows simple function, selection and adjustment.

Upgradeable throughout the range, GasCheck G is available in three distinct versions; G1, G2 and G3 with varied capabilities. Features can be easily added to upgrade the instrument without it having to be returned to the factory.

Feature	<b>G1</b>	G2	G3
Rapid detection of gas leaks			
Measures gas leaks (single gas)			
Measures gas leaks (up to 20 gases)			
Audible sounder			
Flashing back-lit display			
Peak hold readings			
Factory or custom calibration available			
Data logging (store up to 10 readings)			
Readings displayed in cc/sec, g/yr, ppm or mg/m <sup>3</sup>			
Selectable battery type			
Upgradeable			

Key: Standard Feature 📕

The G2 model is factory configurable only, the Gas and measurement units must be specified with the order.

#### Extend your instrument warranty

Your GasCheck G instrument warranty may be extended by simply registering your product on the Ion Science website within one month of purchase. Visit www.ionscience.com/instrument-registration to take advantage of this offer.

#### **Applications include**

Industrial • Quality Assurance • Manufacturing

Laboratory 
Medical 
Research

#### Accessories

GasCheck G is supplied with an exclusive range of accessories. Visit www.ionscience.com/gascheck for more info.

## **Distributed by:**

Authorized Distributor: GasDetectorsUSA.com Houston,Texas USA sales@GasDetectorsUSA.com 832-61-3588

#### **TECHNICAL SPECIFICATION**

#### DETECTOR

Micro thermal conductivity detector (MTCD) Sensor is poison resistant with over range protection

#### OPERATION

Battery Type: 4 x alkaline AA size or NiMH (rechargeable) Typically 40 hours life

#### **SENSITIVITY (cc/sec)** He 1 x 10<sup>5</sup>, CH<sub>4</sub> 5 x 10<sup>5</sup>, R12 5 x 10<sup>5</sup>, Ar 1 x 10<sup>-4</sup>

#### ACCURACY

5% Displayed reading — One digit

#### RESPONSE

T90 = 1 second rise and clear down

#### SOUND

Flashing LED and 90 dBA (at 10 cm) audible sounder

#### CALIBRATION

Factory calibrated to fully documented procedures in accordance with our ISO 9001:2008 Quality Management System

#### DATA LOGGING

10 data points (available for G3 only.)

#### TEMPERATURE

Operating: -20 to +60 °C, -4 to 140 °F Storage: -20 to +70 °C, -4 to 158 °F Humidity: 0 to 99% RH (non-condensing)

FLOW RATE 2 cc/min

#### TEMPERATURE

Operating: -20 to 60 °C, -4 to 140 °F Storage: -20 to 70 °C, -4 to 140 °F Humidity: 0-99% RH (non condensing)

#### WEIGHT & DIMENSIONS

Instrument with probe: 390 x 60 x 49 mm, 15.5 x 2.3 x 1.9" Case: 420 x 320 x 97 mm, 16.5 x 12.5 x 3.8" Instrument: 0.45 kg, 1 lb, Packed 1.6 kg, 3.5 lb

EMC tested EN50081-1 & EN50082-1 July 98.

#### Customer testimonial...

"We have bought several GasCheck G3 units from Ion Science and are really happy with how reliable the ppm readings are - customers find the instrument easy to use. The customer service received from Ion Science is excellent, and so is the company overall. Lee Chamberlain, VP Operations, LACO Technologies

## Manufactured by:

Ion Science Ltd The Way, Fowlmere, Cambs, SG8 7UJ, UK T: +444 (0) 1763 208 503 E: info@ionscience.com www.ionscience.com



