

SAN-10



PERSONAL 5% CO2 SAFETY **MONITOR & DATA LOGGER**

Our #1 CO, Remote Storage Safety Device

The SAN-10 Personal 5% CO₂ Safety Monitor and Data Logger is designed for employees who work in enclosed areas where CO, būildup may cause personal harm.

Features

- Audible, visual strobe light and vibrating alarms
- Man down alarm leverages accelerometer technology
 USB Cable for Charging
- Rugged design with protective rubber enclosure
- Heavy duty metal clip
- Rechargeable Li-Ion battery 72+ hours per charge
- Large LCD Display
 - CO2
 - % Relative Humidity
- Calibrate using nitrogen or ambient air
- IP54 housing protects against dust and rain
- Programmable alarm settings
- Data logging capabilities that can be displayed with our GasLab Software

Includes

- 110/240 VAC USB Wall Adapter
- User Manual

Additional Personal Devices

- SAN-20 Personal O2 Safety Monitor
- SAN-30 Personal CO Safety Monitor



TECHNICAL DATA

Personal 5% CO2 Safety Monitor & Data Logger

CO ₂ Measurement Range	0-5% (0-50,000 ppm)
CO ₂ Measurement	NDIR (Non-dispersive Infrared)
CO ₂ Measurement Interval	2 Seconds
Operational Humidity Range	1-95% RH, non-condensing
Operating Temperature Range	0-50°C (32-122°F)

Specifications

Size	2.0 x 3.75 x 1.0 in. (50.8 x 95.25 x 25.4mm.)
Alarm Level	90 db @ 10 cm
Weight	4 oz.
Sensor Life Expectancy	15 years









