

**integrated
expandable**
calibration gas system

genie

03

Now with added flow
and concentration options!

03

Ozone Calibration Gas

Features

- ▶ Selectable concentrations.
- ▶ Integrated Microprocessor controlled feedback.
- ▶ Compact, portable hand-held design.
- ▶ Simple to use, long life.

Specifications

03	P/N	Flow	Concentration
	750-0202-LT	Fixed 0.3 LPM Fixed 1.0 LPM	up to 1.0 PPM up to 0.4 PPM (.1 PPM increments)
	750-0202-02	Variable	0.2 to 1.0 PPM

Air flow rate (with internal pump)	Fixed or Variable
Source life	500 hours
Warm-up time (to 90%)	Approx. 2 minutes
L x W x H	5"W x 3.88"H x 3.13"D
Weight	2 lb (1360 g)
Operating temperature	0°C to 50°C
Relative humidity (intermittent use)	±100%
Accuracy	±10%
Repeatability	±5%
Battery Power	4 Alkaline 'AA'
Battery Life	6 hours @ .5 LPM



**The GENie 03 Calibration Gas Instrument
is the most accurate source of ozone calibration gas on the market!**



Advanced Calibration Designs, Inc.
2024 W McMillan St. Tucson, AZ 85705 USA
www.goacd.com . acd@goacd.com
520-290-2855 . 800-737-0224