





Ambient Air or O₂ Deficiency

Pipeline Leaks

Food Processing

Oxygen Analyzer

Bacharach's $Oxor^{\circledR}$ III single gas analyzer offers service technicians the easiest and most affordable way to measure O_2 levels. The $Oxor^{\circledR}$ III is a battery powered, handheld instrument that can quickly and accurately measure levels of O_2 between 0 and 20.9 %. Each unit includes batteries and is supplied with a stainless steel probe assembly for remote sampling. The kit includes a wireless IRDA printer which provides a permanent test record of the detected O_2 level.

SPECIFICATIONS	
Range	0 - 20.9 %
Resolution	0.1%
Accuracy	$+0.4 \text{ to } 0.8\% 0_2$
Operating Temp.	Instrument: 32-104°F (0-40°C)
Warm Up Time	60 seconds
Battery Life	Up to 18 hours continuous operation
Display	Four-digit LCD display w/backlight
Power	4 'AA' alkaline batteries
Printer Port	Wireless, IRDA or HP protocol
Weight	16 oz. with batteries
Dimensions	7.5"H x 3.1"W x 2.1" D (190mm x 79mm x 53mm)
Warranty	2 year

ORDERING INFORMATION	
PART NO.	DESCRIPTION
19-8112	Oxor® III includes 4 'AA' batteries, probe and hose assembly, and hard carrying case
19-8113	Oxor® III Kit, includes 4 'AA' batteries, probe and hose assembly and a hard carrying case, plus an IRDA printer
24-1400	IRDA printer with disposable batteries
24-1310	Printer paper, 5 roll package
24-8106	Replacement O ₂ sensor
19-3086	Probe and hose assembly
11-0121	Wool saturator for probe tube (pkg. of 10)

Authorized Distributor: GasDetectorsUSA.com Houston, TX USA 832-615-3588 sales@GasDetectorsUSA.com

