A100SONTEL Telephone Initiated Alarm Sounder

The A100SONTEL is a compact, high output, 100dB(A) telephone initiated alarm sounder.

The line powered A100SONTEL has a choice of three alarm tone frequencies.



Specification:

Nominal output:

Volume control:

Effective range:

Supply:

Colour:

Cable entries:

Terminals:

Weight

Operating temp:

Relative humidity:

Storage temp:

No. of tones:

Features: 100dB(A) @ 1m +/- 3dB • Continuously rated. 3 Max. 100dB(A); Min. 90dB(A) 32m @ 1KHz Direct power from telephone line (REN 1) IP66 Ingress protection: Approvals: Housing material: High impact UL94 V0 & 5VA FR ABS Red (RAL3000), grey (RAL7038) & white. 3 x M20 clearance gland knockouts in side & back 0.5 to 2.5mm² cables. -25 to +55°C -40 to +70°C

AUTHORIZED DISTRIBUTOR: GasDetectorsUSA.com Houston, Texas USA sales@GasDetectorsUSA.com 832-615-3588

Part codes:

Tones:

Tone 1

Tone 2

Tone 3

A100SONTEL[x]

[x] = Housing colour:

G: Grey R: Red W: White

Siren Tone

Alternating tone

Sweeping tone

*SPL data +/-3dB(A). Measured at optimum voltage.

90% at 20°C.

0.26kg



- Stainless steel fixings.
- Unit can be mounted using external lugs or internal
- BESA compatible fixing positions.
- Tropicalisation available on request.

• GOST-R approved. Cert: POCC GB-JB05-H00144

