

# IS-CP4A-PT/IS-CP4B-PT Tool Reset Call Point

The IS-CP4A-PT and IS-CP4B-PT push button, tool resettable, manual call points are approved for Zones 0, 1, 2, 21 & 22 requiring intrinsically safe equipment for the control of fire and gas alarm systems. SIL 2 compliant to IEC 61508 (2010).

The push button mechanism is protected by a spring loaded cover therefore the switch requires a two-action activation. The push button is user resettable via the use of the special key supplied with the unit. The IS-CP4 range features enclosures manufactured from corrosion proof, marine grade, copper free LM6 (A4-13) aluminium which is chromated and powder coated. Available with and without monitoring resistors all versions are certified to ATEX and IECEx standards.

## Options

- Alternative housing colours are available to meet specific requirements.
- Metalised Polyester "Duty" label.
- Series and/or End of Line resistors.

## Approvals

- ATEX certificate: SIRA 09ATEX2287X, EN 60079-0 : 2012, EN 60079-11 : 2012, IEC 60079-26 : 2014, EN 60079-31 : 2014
- IECEx certificate: IECEx SIR 09.0122X, IEC 60079-0 : 2011, IEC 60079-11 : 2011, IEC 60079-26 : 2014, IEC 60079-31 : 2013
- GOST-R certificate: POCC GB.JB05.B03365
- SIL 2 compliant to IEC 61508 (2010)



## Specification

ISCP4A-PT:	II 1G Ex ia IIC T6 Ga II 2D Ex tb IIIC T60°C Db IP66
ISCP4B-PT:	II 1G Ex ia IIC T4 Ga IP66
Ambient:	Ta = -40°C to +55°C [-40° to +131°F]
Ingress protection:	IP66
Enclosure material:	Marine grade copper free LM6 Aluminium
Enclosure finish:	Chromated & powder coated finish: anti-corrosion.
Colour:	RAL3000 Red (others available on request)
Cable entries:	2 x M20 clearance top and 1 x M20 clearance side. Back box can be rotated to give 2 x bottom and 1 x side entries.
Stopping plugs:	2 x nylon plugs as standard Brass and stainless steel plugs optional
Terminals:	6 × 4.0mm <sup>2</sup> cables
Weight:	0.8Kg

## Part Codes

Option:	Code:	Description:
Type:	ISCP4A-PT	A type – no end of line devices
	ISCP4B-PT	B type – choice of end of line devices
Terminals:	ST	ST: Standard 6 × 4mm <sup>2</sup>
Duty label:	NL	No duty label
	DL	Duty label required – specify contents
Colour:	RD	Red enclosure colour
	XX	Other enclosure colour – contact sales
E.O.L. Resistor:	ExxxR	Resistor value in Ohms e.g. E470R = 470 Ohm (only required for ISCP4B type)
Series Resistor:	SxxxR	Resistor value in Ohms e.g. E1K5R = 1.5K Ohm (only required for ISCP4B type)
e.g. ISCP4A-PT-ST-LF-NL-RD ISCP4A Push button call point with 6 × 4mm <sup>2</sup> terminals and no duty label. Red housing		
e.g. ISCP4B-PT-ST-NF-NL-RD-E470R ISCP4B Push button call point with 6 × 4mm <sup>2</sup> terminals, no duty label, with a 470 Ohm end of line resistor. Red housing.		

## Versions

Version:	Input:	Voltage:	Terminals:	Cable entries:
ISCP4A-PT	U <sub>i</sub> = 30V I <sub>i</sub> = 500mA P <sub>i</sub> = 1.1W C <sub>i</sub> = 0 L <sub>i</sub> = 0	250V ac Max. 5.0A Max. 50V dc Max. 1.0A Max.	6 × 4mm <sup>2</sup>	2 x M20 Top/Bottom 1 x M20 Left/Right
<b>Coding:</b>	II 1G Ex ia IIC T6 Ga Ta = - 40°C to +55°C II 2D Ex tb IIIC T60°C Db IP66			
Version:	Input:		Terminals:	Cable entries:
ISCP4B-PT	U <sub>i</sub> = 30V I <sub>i</sub> = 500mA P <sub>i</sub> = 1.1W C <sub>i</sub> = 0 L <sub>i</sub> = 0		6 × 4mm <sup>2</sup>	2 x M20 Top/Bottom 1 x M20 Left/Right
<b>Coding:</b>	II 1G Ex ia IIC T4 Ga Ta = - 40°C to +55°			