



An ammonia sensor that exhibits excellent accuracy and precision

Manning EC-F2 ammonia sensor



Ammonia Specific

- Immediate response to ammonia

User Friendly

- No moving parts
- Factory calibrated
- Requires minimal adjustments after installation

Reliable

- Highly resistant to EMI/RFI
- Available in three ranges
- Minor response to common interference gases
- Negligible response to extreme changes in relative humidity

ATMOS™ Technology

- Allows for operation down to -50°F and in condensing humidity environments or during washdown
- Automatically adapts to its environment and provides accurate and reliable performance under the harshest conditions

Housing

- NEMA 1 #16 gauge heavy-duty steel enclosure
- NEMA 4 available

The Manning EC-F2 Sensor is a three-wire, 4/20 mA sensor for ammonia available in ranges of 0-100 ppm, 0-250 ppm, 0-500 ppm and 0-1,000 ppm.

The Manning EC-P2 exhibits excellent accuracy and precision, with negligible response to common interference gases and dramatic changes in relative humidity. Reliable trip levels as low as 25 ppm can be expected with the 0-100 ppm sensor. The unit exhibits extremely high reliability with no moving parts.

Monitoring equipment must be configured to indicate a fault if the signal is less than 1.5 mA. All signals over 20 mA must be considered a high gas concentration.

Applications

- Meat, poultry, and fish processing facilities
- Dairy and ice cream plants,
- Wineries and breweries
- Fruit juice, vegetable juice, and soft drink processing facilities
- Cold storage warehouses
- Other food processing facilities
- Seafood processing facilities aboard ships
- Petrochemical facilities.



Technical summary



General Specification	
Use	Simple and reliable "gas specific" system that is useful in detecting low ppm levels
Method	Electrochemical (diffusion)
Ranges	0-100 ppm (standard) 0-250 ppm 0-500 ppm 0-1,000 ppm
Common Operation	
Output	Isolated 4/20 mA, 700 ohms max at 24 VDC
Accuracy	± 5% generally, but limited by available calibration gas accuracy
Repeatability	± 2% full scale
Operational	
Humidity	5-100% RH (condensing). ATMOS equipped® enviro-adaptive technology option required for condensing conditions or refrigerated areas, and all outdoor applications.
Temperatures	-50° F to +120° F (-46° C to 49° C) ATMOS equipped® enviro-adaptive technology option required for refrigerated areas or outdoors
Common Module	
Sensor Pressure Limits	0-10 PSIG
Power Source	24 VDC, 0.5 amp max
Gas Sampling	Diffusion method is standard
Weight	3 lbs. (1.4 kg)
Dimensions	6 in. high x 4 in. wide x 3.5 in. deep (15.2 cm x 10.2 cm x 8.9 cm)
Cable Recommendations	#18/3 shielded cable (Belden #8770 or equal), cable runs <1,500 ft. (457 m)
Enclosure	NEMA 1, gasketed, #16-gauge steel (standard). Stainless steel or explosion-proof designs, including modified enclosures for low temperatures, ventilation ducts, etc., are available (contact Manning Systems). Note: The standard EC is for use in non-classified areas only.
Sensor Specifications	
Sensor Pressure	Limits 0-10 PSIG
Response Time	T50 = 10 seconds T100 < 1 second for concentration > 1% NH3
Ranges	0-100 ppm (standard) 0-250 ppm 0-500 ppm 0-1000 ppm
Enclosure	NEMA 1, gasketed, #16 gauge steel (standard). Stainless steel or explosion-proof designs, including modified enclosures for low temperatures, ventilation ducts, etc. are available.
Weight	3 lbs.

Honeywell Analytics Lines of Business



Commercial

Gas detection from standalone units to fully engineered, multi-point systems, all offering cost-effective regulatory compliance

- » Applications: parking structures, chillers, mechanical rooms, office towers, commercial buildings, shopping centers, swimming pools, golf courses, schools and universities, laboratories

Industrial

Renowned Sieger and Manning gas detection systems with advanced electrochemical, infrared and open path sensing technologies

- » Applications: oil and gas, cold storage, water/wastewater treatment, chemicals, engine rooms, plastics and fibers, agriculture, printing and light industrial

Portables

Single or multi-gas Lumidor and other premium detectors with compact, lightweight designs ranging from simple alarm only units to advanced, fully configurable and serviceable instruments

- » Applications: underground utility and electricity ducts, boiler rooms, post-fire sites, sewers, industrial plants, industrial hygiene, first responder teams, remote fleets



High Tech/Government

A complete portfolio of gas and chemical detection instrumentation including infrared spectroscopy (MST) with no cross interference, to Chemcassette paper-based solutions (MDA Scientific) offering detection down to parts per billion

- » Applications: semiconductor manufacturing and nanotechnology, aerospace propulsion and safety, specialty chemicals industry, research laboratories, emergency response

Technical Services

24/7 global network includes post-sales service and Systems Integration teams

- » Emergency call out, service contracts, on/off-site repair, training and commissioning
- » Complete range of spares, consumables and accessories

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Honeywell