



SenSmart 1000 Series



Show with Aluminum "AL" XP model



Shown with Non-metallic Poly "PY" Model



Shown with Stainless Steel Cover

The RC Systems **SenSmart 1100/1200/1300** are complete 2 or 3 wire Gas Detectors available in UL94 flame retardant plastic, or, Class 1 Div 1 316 stainless steel sensor head enclosures. These easy-to-install and maintain gas detectors must be connected to an R. C. Systems single or multi-channel receiver to add user calibration and readout functions. (www.rcsystemsco.com/zoneprotector).

SenSmart 1100 utilizes our electrochemical temperature controlled SMART sensors to transmit O₂, H₂S, SO₂, Cl₂, HF, HCL, NO₂ (to name a few) 2-wire 4-20mA gas values to R. C. Systems single and multi-channel receivers.

The **SenSmart 1200, 1300, 1400** and **1500** utilize our 3-wire direct "bridge" sensor input, including catalytic, PID and infrared, to detect methane, propane, VOC's, benzene, CO₂ and many other compounds. The bridge output is compatible with R. C. Systems single and multi-channel receivers.

FEATURES HIGHLIGHT

- Field swappable sensor module. Range and target gas configured on sensor module
- Improves system noise immunity because low level sensor signals are protected within the sensor head
- Industry standard 4-20mA signal may be transmitted thousands of feet on 2-wires
- 316 SS model is suitable for Class 1 Div 1 hazardous areas.
- Missing or failed sensor forces <2mA FAULT signal
- Compatible with 1, 2, 4, 16 and 64 channel Receiver/Controllers (user calibration & readout are at the Receiver)
- 2-wire milliamp signal is nonpolar with protective "steering diodes"

Power Supply	SenSmart 1100: 9-36 VDC @ 25mA 9-36 VDC @ 25mA SenSmart 1200, 1300, 1400 and 1500: 3-wire direct "bridge" sensor 2-4.25 VDC sensor specific
Accuracy	+/- 1% of full scale range (typical)
Standard Output	SenSmart 1100 : Standard 2-wire 4-20mA current sink . Max loop Resistance is 600 ohms with nominal 24VDC power supply SenSmart 1200, 1300, 1400 and 1500: 3-wire direct "bridge" sensor output
Temp	Less than .1% per degree C over ambient temperature range
Housing	316 Stainless or aluminum enclosure suitable for Class 1 Groups A,B,C,D; Class 2, Groups E,F,G, UL94 Poly Black Plastic Enclosure
Approval	Division 1 and 2 Group A,B,C,D Exia. Suitable for Explosion Proof and Intrinsically Safe installations UL94 Poly Black Plastic Enclosure: Non-Incendive Cl 1 Div 2 Gr ABCD

