

# FIRE ALARM PULL STATIONS



## RMS-EX-WP Series

### Explosion and weather proof fire alarm pull stations

The Tomar RMS-EX-WP manual pull stations are designed to operate in hazardous locations and harsh environmental conditions. They are NEMA 4X rated, and UL listed for use in Class I, Division I, Groups B, C, and D; Class II, Division I, Groups E, F, and G; and Class III locations.

- Explosion proof, Class 1, Division 1
- Weather proof (NEMA Type 4X)
- Single or Dual Action
- Break Glass
- Lift and Pull
- Terminal strip or Pigtail connection
- 9 different colors
- Custom lettering available in any language
- Single or Double contact
- ULC listed and FM Approved

The RMS-EX-WP stations are made entirely in the U.S.A. of the finest materials and workmanship available. The high-strength metal die-cast alloy will provide many years of dependable service in even the harshest industrial environments. All components are pre-painted or have plated surfaces to inhibit corrosion. The model RSM-EX-WP pull stations are suitable for hazardous areas due to the presence of flammable gases or vapors, combustible dust, or easily ignitable fibers or fillings. Installation at petroleum refineries, offshore oil and gas production and processing facilities, chemical and petrochemical plants, storage areas and other processing facilities where hazardous substances are handled or stored.

Tomar Single Action manual pull stations are activated quickly and easily by pulling down the T-handle. Dual Action Lift and Pull and Break Glass are available to minimize accidental or malicious alarm activations.

Electrically the Tomar pull station is unbeatable with 10 amp snap action switch offered in all possible contact arrangements (including gold contacts). Tomar pull stations can be used with or without the included glass rod, with replacement requiring no special tools.

## RMS-EX-WP Ordering Information

Model	Description
RMS-6T-EXP-WP	D.P.D.T. with Terminal connection

## Specifications

Item	Description
UL Rating	NEMA Type 4X outdoor
Contacts	D.P.D.T. (double pole double throw)
Contact Rating	10 amps @ 125/250 VAC.
Operating Temperature	-35° C to 65° C
Wire AWG	12 to 22 AWG
Wiring	Terminal block
Construction	Metal
Waterproof Mounting Box	1/2" Conduit Entrance; Hardware & instructions included
Dimensions Single Action	Width - 3.2in    Height - 4.75in    Depth - 5in    Weight - 3 lb
Dimensions Dual Action, Lift and Pull (LP)	Width - 3.2in    Height - 4.75in    Depth - 5.3in    Weight -3.1 lb
Dimensions Dual Action, Break Glass (DAH)	Width - 3.2in    Height - 4.75in    Depth - 5.5in    Weight - 3.6 lb
Available Colors	Red, Blue, Green, Yellow, White, Black, Gray, Purple, Orange

### Options – please add at time of order

- /KL    Key lock plus keys
- /Color option – Please specify color if other than Red

### Accessories

- GR    Replacement glass rods
- GP    Replacement glass
- LP    Lift and Pull cover
- DAH   Break glass adapter

### How to Order:

- Specify model number
- Specify options, special lettering, and color if other than Red

### Architect and Engineer Specifications

The manual pull station shall be Tomar series RMS-EX or approved equal. The pull station shall be NEMA 4X rated and ULC listed for use in Class I, Division I, Groups B, C, and D; Class II, Division I, Groups E, F, and G; and Class III locations. The pull station must be made of high-strength metal die-cast alloy. Single action model activation shall be by T-handle pull-down function. Dual action model activation shall be by Lift and Pull cover, or Break Glass action. The pull station must be able to be activated either with or without a glass rod, which must be field-replaceable and requiring no special tools. The pull station must include a double throw switch and terminal block design.